article#	**293-11v**
article description	**CEE-connector 32A 3p 24/42VAC >400-500Hz IP44 TWIST**
description long	CEE-connector 32A 3p 24/42VAC >400-500Hz IP44 TWIST housing material: PA6 rated current: 32A number of poles: 3 (3P) clock-position: 11h rated voltage/frequency: 24/42V~ / >400-500Hz contacts: brass nickel plated connection technology: screw terminals IP protection class: IP44
GTIN (EAN)	9003399400001
country of origin	AT
customs number	85366990
net weight	0.177 kg
packaging quantitiy	10
minimum order quantitiy	10

ETIM 9.0	EC001320
IEC-amperage	32 A
Number of poles	3
Voltage according to EN 60309-2	20-25 V / 40-50 V (>400-500 Hz) green
Clock hour position	11 h
Identification colour	Green
Degree of protection (IP)	IP44
Connection system	Screwed terminal
Angle of plug	Straight
Cable entry	Gland nut
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Nickel-plated

a	150 mm
b	75 mm
K (cable Ø)	9,5-24 mm
SW	48 mm
wire flexible	1-10 mm²
contact screws	160 Ncm
strain relief	600 Ncm
dismantling length	70 mm
stripping length	14-16 mm
ambient temperature	-25 – 40 °C
temperature resistance	-25 – 80 °C



https://www.pcelectric.at/shop/en/?func=detail&artnr=293-11v

Changes and printing errors reserved!

8/2/2023